



Conforme alle direttive
Compliance to:
 2006/95/CE Low voltage
 2004/108/CE Electromagnetic Compatibility
 1999/5/CE R&TTE

Norme di riferimento
Reference standards:
 EN60950-1:2006
 EN60730-1:2011
 EN61000-4-2:2011
 EN61000-4-3:2006
 EN 301 489-1 ver.1.9.2:2011-09
 EN 301 489-7 ver.1.3.1:2005-11
 EN 301 511 ver. 9.02:2003-03

Alimentazione	12Vdc (min 9Vdc, max 14Vdc)
Assorbimento	3.5W Max
Frequenza	850 - 900 - 1800 -1900 MHz Quad Band
Tipo antenna	Stilo avvitabile SMA M
n°2 ingressi digitali	Configurabili N.O. / N.C.
n°1 sonda interna	NTC 10K @25°C ±1%
n°1 sonda esterna	NTC 10K @25°C ±1% (opzionale)
n°2 uscite relé	2 x 3A @ 400 Vac
n°1 connettore USB	micro USB (tipo B) (presente a seconda della versione hardware)
Lunghezza fili sonda esterna	3m max, oppure fino a 25 m con cavo schermato
Risoluzione temperatura	0.1°C
Isteresi allarmi temperatura	2.0 °C (per 60 sec)
Campo di misura sonda interna	0.0 .. 105.0 °C
Campo di misura sonda esterna	-35.0 .. 105.0 °C
Campo di misura	-20.0 .. 55.0 °C
Batterie tampone	3xAAA NiMh 1,2V 800..1000 mAh
Temperatura funzionamento	-20 .. +55.0 °C
Temperatura stoccaggio	-20 .. +55.0 °C
Limiti umidità	20 .. 80 % RH non condensante
Grado di protezione	IP40 sul frontale - IP 20 sui morsetti
Contenitore - Materiale	PPO autoestinguento
Colore	RAL 7035 (Grigio Luce)
Peso	~ 575 gr.
Dimensioni	4 moduli DIN
Installazione	Montaggio su guida DIN

Power Supply	12Vdc (min 9Vdc, max 14Vdc)
Absorption	3.5W Max
Frequency	850 - 900 - 1800 -1900 MHz Quad Band
Antenna type	Stilo screw SMA M
n°2 digital inputs	Configurable N.O. / N.C.
n°1 internal probe	NTC 10K @25°C ±1%
n°1 external probe	NTC 10K @25°C ±1% (optional)
n°2 output relays	2 x 3A @ 400 Vac
n°1 USB connector	micro USB (type B) (present depending on the hardware version)
Length wires external probe	3m max, or up to 25 m with shielded cable
Temperature resolution	0.1°C
Temperature alarms hysteresis	2.0 °C (for 60 sec)
Measuring range internal probe	0.0 .. 105.0 °C
Measuring range external probe	-35.0 .. 105.0 °C
Measuring range	-20.0 .. 55.0 °C
Backup batteries	3xAAA NiMh 1,2V 800..1000 mAh
Operating temperature	-20 .. +55.0 °C
Storage temperature	-20 .. +55.0 °C
Humidity limits	20 .. 80 % RH non-condensing
Protection	IP40 frontal - IP 20 terminals
Case - Material	PPO self-extinguishing
Color	RAL 7035 (Light Grey)
Weight	~ 575 gr.
Dimensions	4 modules DIN
Installation	Mounting on rail DIN